



Aircraft Deicing Inc.

833-334-2464

www.aircraftdeicinginc.com

C25PS Anti-icing Cart

- Cart mobility provided by hand, ATV, tractor, etc.
- **New** Heavy Duty welded channel frame w/ 5" caster nose wheel.
- 12 volt diaphragm pump w/ pressure demand switch
- Factory set pressure demand switch: 50 – 60 psi.
- Pressure gauge (0 - 100 PSI)
- 25 gallon corrosion resistant polyethylene tank
- 25' of 3/8" ID high pressure hose
- GunJet handgun with 24" extension
- **New** 16x6.5-8 turf tread tires
- 90 day warranty



The **12-Volt Electrically Powered Carts** are appropriate for either indoor or outdoor use, and are typically used for anti-icing operations using SAE Type IV anti-icing fluid. These carts use a 12-volt, 3-chamber diaphragm, non-circulating pump with a demand pressure switch that provides fluid flow rates of up to 4.5 gpm/60 PSI. Because these carts can be used in a hanger, provide lower fluid pressure and flow rates (vs the gasoline engine powered carts), and use a non-circulating pump (to avoid viscosity degradation of SAE Type IV fluid), they are particularly suitable for anti-icing operations prior to moving the aircraft outdoors. All carts are supplied complete including a steel frame, self containment kit, tow bar with pintel ring, main wheels, pump, tank, pressure gauge, high-pressure hose, pistol-grip handgun, and semi-fan, flat pattern brass nozzle. The on-board charging & battery system makes these units completely self-contained.

Product Details

Tank Capacity	25 gallons
Tank Material	Polyethylene
Pump Type	Diaphragm
Pump Amps – Max	7.0 Amp
Pump output - Max	4.5 GPM
Pump Pressure - Max	60 PSI Max pressure
Sprayer Gun	High-Pressure Deluxe Pistol-Grip Handgun
Main Tires	16x6.5-8 Turf Tread Tires
Nose wheel	5" Swivel
Hitch	24" Hinged Tow Bar with Pintel Ring
Self Containment Kit	On-board Battery and Battery Charger