



## C25PS-D De-icing/Anti-icing Cart

- Cart mobility provided by hand, ATV, tractor, etc.
- Heavy Duty Steel Channel frame with 5" swivel caster nose wheel.
- 12 volt diaphragm pump w/ pressure demand switch
- Factory set pressure demand switch: 50 – 60 psi.
- 120 volt, 2000w Immersion Heater
- Pressure gauge (0 - 100 PSI)
- 25 gallon corrosion resistant Polyethylene tank
- 25' of 3/8" ID high pressure hose
- GunJet handgun with 24" brass extension
- 16 x 6.5 -8 Pneumatic Turf Tread tires
- 90 day warranty



The **12-Volt Electrically Powered Carts** are appropriate for either indoor or outdoor use. These carts use a small 12-volt, 3-chamber diaphragm, non-circulating pump with a demand pressure switch that provides fluid flow rates of up to 4.5gpm/60 psi. The cart is equipped with an electric immersion heater to heat the de-icing fluid to a maximum of 140°F to help melt frost, snow & ice from your aircraft's surfaces. All carts are supplied complete including a steel frame, immersion heater, two Turf Tread Tires, pump, tank, pressure gauge, temperature gauge, 25' high-pressure hose, deluxe pistol-grip handgun, and brass nozzle. The on-board charging and battery system makes these units completely self contained.

### Product Details

Tank Capacity	25 gallons
Tank Material	Corrosion-Resistant Polyethylene Tank
Heating Element	2000w 12 volt Immersion Heater
Pump Type	Diaphragm
Pump Amps – Max	7.0 Amp
Pump output - Max	4.5 GPM
Pump Pressure -	60 PSI Max pressure
Max Sprayer Gun	High-Pressure Deluxe Pistol-Grip
Immersion Heater	Handgun 120 volt, 1400 watt
Main Tires	16 x 6.5 -8
Nose wheel	5" swivel caster
Hitch	24" steel tow bar with pintel ring
Self Containment Kit	On-board Battery and Battery Charger



# Aircraft Deicing Inc.

833-334-2464

[www.aircraftdeicinginc.com](http://www.aircraftdeicinginc.com)

## C40GPS De-icing Cart

**40 gallon de-icing cart with a Honda 5.5 HP engine, 2000 watt immersion heater, temperature gauge, nose wheel, and tow bar.**



Our gas powered 40 gallon cart is designed for outdoor de-icing operations. This cart uses a 5.5 HP air-cooled gasoline engine, providing adjustable fluid flow rates and pressures of up to 7 GPM/150 PSI, sufficient to de-ice all general aviation, corporate & charter aircraft. The cart is equipped with an electric immersion heater to heat the de-icing fluid to a maximum of 140°F to help melt frost, snow & ice from your aircraft's surfaces.

All carts are supplied complete, including steel frame, 40 gallon polyethylene tank, 5.5 HP Honda gas engine, immersion heater, temperature gauge, pump, adjustable pressure value, pressure gauge, 25' high-pressure hose, deluxe pistol-grip handgun with 24" brass extension and brass nozzle, hitch bracket, main wheels, nose wheel and tow bar.

### Product Details

Tank Capacity	40 gallons
Tank Material	Corrosion-Resistant Polyethylene Tank
Engine	Honda 5.5 HP
Pump Type	6-Roller Cast Iron Pump
Pump Output	7 GPM
Pump Pressure	150 PSI Max Pressure
Immersion Heater	120 Volt, 2000 Watt,
Max fluid temp	140°F
Hose	25 LF 3/8" High Pressure Hose
Sprayer Gun	High-Pressure Deluxe Pisto-Grip Handgun
Main Tires	16 x 6.50 -8, Turf Tread
Nose Wheel	5" Swivel Caster
Hitch	24" Tow Bar with Pintel Ring